

INTERNATIONAL ELECTROTECHNICAL COMMISSION **IEC Certification Scheme for Explosive Atmospheres**

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEx BAS 05.0026X

issue No.:2

Certificate history:

Status:

Current

Issue No. 2 (2010-6-22) Issue No. 1 (2009-6-5) Issue No. 0 (2005-7-4)

Date of Issue:

2010-06-22

Page 1 of 4

Applicant:

Don Electronics Limited

Westfield Industrial Estate

Kirk Lane Yeadon Leeds LS19 7LX

United Kingdom

Electrical Apparatus:

Optional accessory:

'Elite' range of grey plastic enclosures, complete with sensor circuits

Type of Protection:

Enclosure

Marking:

IECEx BAS 05.0026X

Ex tb IIIC T125°C Db IP66 Tamb -20°C to +50°C

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

Position:

Managing Director

Signature:

(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.

This certificate is not transferable and remains the property of the issuing body.
 The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa Rockhead Business Park Staden Lane Buxton Derbyshire **SK17 9RZ United Kingdom**



0



Certificate No.:

IECEx BAS 05.0026X

Date of Issue:

2010-06-22

Issue No.: 2

Page 2 of 4

Manufacturer:

Don Electronics Limited Westfield Industrial Estate

Kirk Lane Yeadon Leeds LS19 7LX

United Kingdom

Manufacturing location(s);

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended,

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2007-10

Explosive atmospheres - Part 0:Equipment - General requirements

Edition: 5

IEC 60079-31: 2008

Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure 't'

Edition: 1

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

IECEx ATR: UK/BAS/04/0894 GB/BAS/ExTR10.0127/00 File Reference:

04/0894 10/0088



Certificate No.:

IECEx BAS 05,0026X

Date of Issue:

2010-06-22

Issue No.: 2

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The enclosure is manufactured in plastic. The enclosure consists of an opaque grey body and transparent/clear lid, complete with silicone sponge gasket that is fitted in a rectangular groove in the lid. The lid is hinged to the body and secured by two stainless steel screws. The body has raised threaded bosses in the base to allow the securing of internal components/circuits. The enclosure has an ingress protection rating of IP66.

The enclosure may be fitted with one or more sensor circuits with a variety of different functions and circuit options. There must be a minimum of 10mm between the components and the enclosure wall.

The Maximum Power Dissipation for the type 864A and 1084B enclosure is 12 Watts per circuit with each circuit within the enclosure being protected by a combination of fuse and zener diodes. The zener diode has a voltage rating which is selected to be as close as possible to the supply voltage.

The 1084B enclosure may be fitted with an alternative internal certification label.

CONDITIONS OF CERTIFICATION: YES as shown below:

This enclosure is a static hazard and shall only be cleaned with a damp cloth.



Certificate No.:

IECEx BAS 05.0026X

Date of Issue:

2010-06-22

Issue No.: 2

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Variation 2.1

To allow an alternative external key pad.

Variation 2.2

To confirm that the equipment covered by this certificate has been reviewed against the requirements of EN 60079-0: 2009 and IEC 60079-31: 2009 in respect of the differences from IEC 61241-1-1:1999, and that none of these differences in the Standard affects this equipment other than the marking.

The marking will change as follows:

Ex tb IIIC T125°C Db IP66 Tamb -20°C to +50°C

ExTR: GB/BAS/ExTR10.0127/00

File Reference: 10/0088



INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEx BAS 05.0026X

issue No.:1

Certificate history:

Status:

Current

Issue No. 1 (2009-6-5) Issue No. 0 (2005-7-4)

Date of Issue:

2009-06-05

Page 1 of 4

Applicant:

Don Electronics Limited Westfield Industrial Estate

Kirk Lane Yeadon Leeds LS19 7LX

United Kingdom

Electrical Apparatus:

Optional accessory:

'Elite' range of grey plastic enclosures, complete with sensor circuits

Type of Protection:

Enclosure

Marking:

IECEX BAS 05.0026X

DIP DIP A21 TA125°C IP66 -20°C < ta < +50°C

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

Position:

Managing Director

Signature:

(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa
Rockhead Business Park
Staden Lane
Buxton
Derbyshire
SK17 9RZ
United Kingdom





Certificate No.:

IECEx BAS 05.0026X

Date of Issue:

2009-06-05

Issue No.: 1

Page 2 of 4

Manufacturer:

Don Electronics Limited Westfield Industrial Estate

Kirk Lane Yeadon Leeds LS19 7LX

United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 61241-1-1: 1999

Edition: 2

Electrical apparatus for use in the presence of combustible dust - Part 1-1: Electrical apparatus protected by enclosures and surface temperature limitation - Specification for

apparatus

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

IECEx ATR: UK/BAS/04/0894

File Reference:

04/0894



Certificate No.:

IECEx BAS 05,0026X

Date of Issue:

2009-06-05

Issue No.: 1

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The enclosure is manufactured in plastic. The enclosure consists of an opaque grey body and transparent/clear lid, complete with silicone sponge gasket that is fitted in a rectangular groove in the lid. The lid is hinged to the body and secured by two stainless steel screws. The body has raised threaded bosses in the base to allow the securing of internal components/circuits. The enclosure has an ingress protection rating of IP66.

The enclosure may be fitted with one or more sensor circuits with a variety of different functions and circuit options. There must be a minimum of 10mm between the components and the enclosure wall.

The Maximum Power Dissipation for the type 864A and 1084B enclosure is 12 Watts per circuit with each circuit within the enclosure being protected by a combination of fuse and zener diodes. The zener diode has a voltage rating which is selected to be as close as possible to the supply voltage.

The 1084B enclosure may be fitted with an alternative internal certification label.

CONDITIONS OF CERTIFICATION: YES as shown below:

This enclosure is a static hazard and shall only be cleaned with a damp cloth.



Certificate No.:

IECEx BAS 05.0026X

Date of Issue:

2009-06-05

Issue No.: 1

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for Issues 1 and above):

Variation 1.1

This document permits existing information (for example on Schedule Drawings) to be replaced by the revised certificate holders name and address. No other changes may be made to the certified design



INTERNATIONAL ELECTROTECHNICAL COMMISSION **IEC Certification Scheme for Explosive Atmospheres**

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEx BAS 05.0026X

Issue No.: 0

Status:

Current

Date of Issue:

2005-07-04

Page 1 of 3

Applicant:

Wheat Electronics Limited

Unit 4

108 Hookstone Chase

Harrogate North Yorkshire HG2 7HS

United Kingdom

Electrical Apparatus: 'Elite' range of grey plastic enclosures, complete with sensor circuits

Optional accessory:

Type of Protection:

Enclosure

Marking:

IECEX BAS 05.0026X

DIP DIP A21 TA125°C IP66 -20°C < ta < +50°C

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

Position:

Signature:

(for printed version)

Date:

Managing Director

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa (2001) Ltd.

Rockhead Business Park Staden Lane **Buxton** Derbyshire **SK17 9RZ United Kingdom**





Certificate No.:

IECEX BAS 05.0026X

Date of Issue:

2005-07-04

Issue No.: 0

Page 2 of 3

Manufacturer:

Wheat Electronics Limited

Unit 4

108 Hookstone Chase

Harrogate North Yorkshire HG27HS **United Kingdom**

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacture'rs quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 61241-1-1: 1999

Edition: 2

Electrical apparatus for use in the presence of combustible dust - Part 1-1: Electrical apparatus protected by enclosures and surface temperature limitation - Specification for

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

IECEX ATR:

File Reference:

UK/BAS/04/0894

04/0894



Certificate No.:

IECEX BAS 05.0026X

Date of Issue:

2005-07-04

Issue No : 0

Page 3 of 3

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The enclosure is manufactured in plastic. The enclosure consists of an opaque grey body and transparent/clear lid, complete with silicone sponge gasket that is fitted in a rectangular groove in the lid. The lid is hinged to the body and secured by two stainless steel screws. The body has raised threaded bosses in the base to allow the securing of internal components/circuits. The enclosure has an ingress protection rating of IP66.

The enclosure may be fitted with one or more sensor circuits with a variety of different functions and circuit options. There must be a minimum of 10mm between the components and the enclosure wall.

The Maximum Power Dissipation for the type 864A and 1084B enclosure is 12 Watts per circuit with each circuit within the enclosure being protected by a combination of fuse and zener diodes. The zener diode has a voltage rating which is selected to be as close as possible to the supply voltage.

The 1084B enclosure may be fitted with an alternative internal certification label.

CONDITIONS OF CERTIFICATION: YES as shown below:

This enclosure is a static hazard and shall only be cleaned with a damp cloth.

Annexe: